Saw Blades









Spline Products



Flat Pool Screen Spline

Black vinyl Flat Spline is used to attach screening material to screen frame. Ideal for porch screen frames. Compatible with aluminum or fiberglass screening Flexible vinyl construction Holds screening in frame



Round Smooth Hollow Spline

Black vinyl Round Smooth Hollow screen spline is used to hold screen material to window and screen door frames. Round, Smooth, hollow core Black Used to hold screen material to window and screen door frames









Peel & Seal® PowerBond™ White 250

Peel & Seal® PowerBond™ White 250 is the ideal choice to tape seams on insulated aluminum panels to create a lasting, waterproof bond. It is also an excellent choice as a flashing material, for roof and gutter repair, window flashing and as a general purpose waterproofing membrane. The product can be applied in temperatures as low as 25°F, perfect for low temperature applications. After installation, Peel & Seal® PowerBond™ White 250 may be exposed to sunlight indefinitely.

Peel & Seal® PowerBond™ White 250

- Features a patented PowerBond[™] adhesive system
- · Excellent waterproof/weatherproof membrane
- Available in 4" or 6" widths by 50' length rolls
- · Aggressively sticks to most surfaces
- Single-ply installation
- · Puncture and abrasion resistant
- Flexible design to conform to odd shapes
- · Lightweight, easy to handle and install
- Compatible with EPDM roofs by utilizing an MFM-approved EPDM primer.
- 15-Year limited warranty

The key to the effectiveness of Peel & Seal® PowerBond™ White 250 is a highly aggressive asphalt adhesive that is combined with a UV stable outer film to form a long-lasting protective barrier. The product is thinner than Peel & Seal®, making it easier to install while having the same performance values. Peel & Seal® PowerBond™ White 250 – the ultimate choice!



Peel & Seal® PowerBond™ White 250 utilizes the same benefits of Peel & Seal®, but is designed specifically to tape seams on insulated aluminum panels.









Peel & Seal® PowerBond™ White 250 installs in just four easy steps.

(1) Wipe surface clean with acetone. (2) Peal back release liner.

(3) Apply to seam of panels. (4) Roll seam for a tight and secure seal.

Peel & Seal®

A self-stick, rolled roofing membrane perfect for low slope applications, patching repairs and forming around protrusions. Single-ply, one-step installation directly to the roof deck. May be left exposed indefinitely.







WE NOW HAVE

#304 STAINLESS SCREWS

IN STOCK



<SS-304> 1/4x2-1/4 Concr Screw BRZ

<SS-304> 1/4x2-1/4 Concr Screw WHT

<SS-304> 1/4x3 Concr Screw BRZ

<SS-304> 1/4x3 Concr Screw WHT

<SS-304> 1/4x5 Concr Screw BRZ

<SS-304> 1/4x5 Concr Screw WHT

<SS-304> 3/8x5 LDT Concr Screw BRZ <SS-304> 3/8x5 LDT Concr Screw WHT

<SS-304> 3/8x7 LDT Concr Screw BRZ

<SS-304> 3/8x7 LDT Concr Screw WHT

<SS-304> 10x2 SMS BRZ

<\$\$-304> 10x2 SM\$ WHT

<\$\$-304> 10x3 SMS BRZ

<\$\$-304> 10x3 SMS WHT

<SS-304> 12x3/4 TEK Screw BRZ

<SS-304> 12x3/4 TEK Screw WHT

<SS-304> 14x1 TEK Screw BRZ

<SS-304> 14x1 TEK Screw WHT



WE NOW HAVE 1X19 -- 1/8" 316 STAINLESS STEEL MARINE GRADE CABLE





